

## 5 CLAIMS:

What is claimed is:

1. A software system for directing product selection over a communication network where a user system receives screen signals from the communication network and displays corresponding screens to a user, the user provides user inputs to the user  
 10 system in response to the screens, the user system transfers corresponding user input signals over the communication network, and the screens are arranged in a sequence, the software system comprising:

user data software configured to direct a processing system to process user data from the user input signals to determine if the user data is consistent data that  
 15 is consistent with at least one of a plurality of products;

screen control software configured to direct the processing system to process user screen selections from the user input signals, transfer a selected one of the screen signals corresponding to a selected one of the screens if the selected one of the screens is backward in the sequence or if all previous ones of the  
 20 screens in the sequence prior to the selected one of the screens have the consistent data, and to transfer to the user system over the communication network an earliest one of the screen signals corresponding to an earliest one of the screens in the sequence that does not have the consistent data if the selected one of the screens is forward in the sequence and if the previous ones of the screens in  
 25 the sequence prior to the selected one of the screens do not all have the consistent data; and

a storage system that stores the user data software and the screen control software.

- 5 2. The software system of claim 1 wherein the screen control software is configured to direct the processing system to include in the screen signals the consistent data for a current one of the screens corresponding to a current one of the screen signals being transferred and the consistent data for earlier ones of the screens in the sequence.

10

3. The software system of claim 1 wherein:

the user data software is configured to direct the processing system to remove from product selection consideration non-selectable ones of the products that are inconsistent with the consistent data; and

15

the screen control software is configured to direct the processing system to modify the screens signals to indicate user data selections that are inconsistent with selectable ones of the products that remain under product selection consideration.

20

4. The software system of claim 1 wherein the user data software is configured to direct the processing system to start with a pre-existing set of the consistent data.

5. The software system of claim 1 wherein the user data software is configured to direct the processing system to complete a purchase transaction for a selected one of the products.

25

6. The software system of claim 1 wherein the products comprise flow meters.

7. The software system of claim 1 wherein the products comprise Coriolis flow

30

meters.

5 8. The software system of claim 1 wherein the products comprise densitometers.

9. The software system of claim 1 wherein the user data indicates a fluid name.

10. The software system of claim 1 wherein the user data indicates at least one of:

10 fluid flow rate, fluid density, fluid viscosity, fluid pressure, and fluid temperature.

11. The software system of claim 1 wherein the user data indicates a flowmeter sensor type.

15 12. The software system of claim 1 wherein the user data indicates a flowmeter process connection type.

13. The software system of claim 1 wherein the user data indicates a flowmeter transmitter type.

5 14. A server system for directing product selection over a communication network  
 where a user system receives screen signals from the communication network and  
 displays corresponding screens to a user, the user provides user inputs to the user  
 system in response to the screens, the user system transfers corresponding user  
 input signals over the communication network, and the screens are arranged in a  
 10 sequence, the server system comprising:

a network interface configured to transfer the screen signals to the  
 communication network and to receive the user input signals from the  
 communication network; and

a processing system configured to process user data from the user input  
 15 signals to determine if the user data is consistent data that is consistent with at  
 least one of a plurality of products, process user screen selections from the user  
 input signals, transfer a selected one of the screen signals corresponding to a  
 selected one of the screens if the selected one of the screens is backward in the  
 sequence or if all previous ones of the screens in the sequence prior to the  
 20 selected one of the screens have the consistent data, and to transfer to the user  
 system over the communication network an earliest one of the screen signals  
 corresponding to an earliest one of the screens in the sequence that does not have  
 the consistent data if the selected one of the screens is forward in the sequence  
 and if the previous ones of the screens in the sequence prior to the selected one of  
 25 the screens do not all have the consistent data.

15. The server system of claim 14 wherein the processing system is configured to  
 include in the screen signals the consistent data for a current one of the screens  
 corresponding to a current one of the screen signals being transferred and the  
 30 consistent data for earlier ones of the screens in the sequence.

5 16. The server system of claim 14 wherein the processing system is configured to  
remove from product selection consideration non-selectable ones of the products  
that are inconsistent with the consistent data, and modify the screens signals to  
indicate user data selections that are inconsistent with selectable ones of the  
products that remain under product selection consideration.

10

17. The server system of claim 14 wherein the processing system is configured to  
start with a pre-existing set of the consistent data.

18. The server system of claim 14 wherein the processing system is configured to  
15 complete a purchase transaction for a selected one of the products.

19. The server system of claim 14 wherein the products comprise flow meters.

20 20. The server system of claim 14 wherein the products comprise Coriolis flow  
meters.

21. The server system of claim 14 wherein the products comprise densitometers.

22. The server system of claim 14 wherein the user data indicates a fluid name.

25

23. The server system of claim 14 wherein the user data indicates at least one of:  
fluid flow rate, fluid density, fluid viscosity, fluid pressure, and fluid temperature.

24. The server system of claim 14 wherein the user data indicates a flowmeter  
30 sensor type.

5 25. The server system of claim 14 wherein the user data indicates a flowmeter process connection type.

26. The server system of claim 14 wherein the user data indicates a flowmeter transmitter type.

10

27. A method of operating a server system for directing product selection over a communication network where a user system receives screen signals from the communication network and displays corresponding screens to a user, the user provides user inputs to the user system in response to the screens, the user system transfers corresponding user input signals over the communication network, and the screens are arranged in a sequence, the method comprising:

processing user data from the user input signals to determine if the user data is consistent data that is consistent with at least one of a plurality of products;

processing user screen selections from the user input signals;

20

transferring a selected one of the screen signals corresponding to a selected one of the screens if the selected one of the screens is backward in the sequence or if all previous ones of the screens in the sequence prior to the selected one of the screens have the consistent data; and

transferring to the user system over the communication network an earliest

25

one of the screen signals corresponding to an earliest one of the screens in the sequence that does not have the consistent data if the selected one of the screens is forward in the sequence and if the previous ones of the screens in the sequence prior to the selected one of the screens do not all have the consistent data.

- 5 28. The method of claim 27 further comprising including in the screen signals the consistent data for a current one of the screens corresponding to a current one of the screen signals being transferred and the consistent data for earlier ones of the screens in the sequence.
- 10 29. The method of claim 27 further comprising removing from product selection consideration non-selectable ones of the products that are inconsistent with the consistent data, and modifying the screens signals to indicate user data selections that are inconsistent with selectable ones of the products that remain under product selection consideration.
- 15 30. The method of claim 27 further comprising starting the method with a pre-existing set of the consistent data.
31. The method of claim 27 further comprising completing a purchase transaction
- 20 for a selected one of the products.
32. The method of claim 27 wherein the products comprise flow meters.
33. The method of claim 27 wherein the products comprise Coriolis flow meters.
- 25 34. The method of claim 27 wherein the products comprise densitometers.
35. The method of claim 27 wherein the user data indicates a fluid name.

5 36. The method of claim 27 wherein the user data indicates at least one of: fluid flow rate, fluid density, fluid viscosity, fluid pressure, and fluid temperature.

37. The method of claim 27 wherein the user data indicates a flowmeter sensor type.

10

38. The method of claim 27 wherein the user data indicates a flowmeter process connection type.

39. The method of claim 27 wherein the user data indicates a flowmeter transmitter type.

15